

GAS DETECTION

SOLO GAS DETECTORS

- Easy-to-service, single-gas detector
- Lightweight convenience
- High standards of sensor quality and reliability
- Compatible with IntelliDoX
- Bump testing (qualitative function check) of the sensors, is a recommended function and requires test gas cylinders and bump test accessories

WIRELESS MODELS

- Provides real-time visibility into the status and safety of hazardous-area workers
- Connected Bluetooth low energy (BLE) capabilities
- Wireless feature allows access from any device with an internet connection to get remote visibility on worker safety and location

Honeywell



Yellow Model No.	Mfg. No.	Black Model No.	Mfg. No.	Hazard	Measuring Range	Price /Each
STANDARD						
HZ329	BWS-C-Y	HZ346	BWS-C-B	Cl ₂	0 ppm to 100 ppm	
HZ330	BWS-V-Y	HZ347	BWS-V-B	ClO ₂	0 ppm to 100 ppm	
HZ331	BWS-ML-Y	HZ348	BWS-ML-B	CO	0 ppm to 2000 ppm	
HZ332	BWS-M2-Y	HZ349	BWS-M2-B	CO	0 ppm to 2000 ppm	
HZ333	BWS-E-Y	HZ350	BWS-E-B	ETO	0 ppm to 50 ppm	
HZ334	BWS-R-Y	HZ351	BWS-R-B	H ₂	0 ppm to 1 ppm	
HZ335	BWS-HL-Y	HZ352	BWS-HL-B	H ₂ S	0 ppm to 100 ppm	
HZ336	BWS-H2-Y	HZ353	BWS-H2-B	H ₂ S ext range	0 ppm to 1000 ppm	
HZ337	BWS-Z-Y	HZ354	BWS-Z-B	HCN	0 ppm to 100 ppm	
HZ338	BWS-A-Y	HZ355	BWS-A-B	NH ₃	0 ppm to 200 ppm	
HZ339	BWS-A2-Y	HZ356	BWS-A2-B	NH ₃ ext range	0 ppm to 500 ppm	
HZ340	BWS-N-Y	HZ357	BWS-N-B	Nitric Oxide	0 ppm to 250 ppm	
HZ341	BWS-D-Y	HZ358	BWS-D-B	NO ₂	0 ppm to 100 ppm	
HZ342	BWS-XL-Y	HZ359	BWS-XL-B	O ₂	0 v/v to 0.3 v/v	
HZ343	BWS-G-Y	HZ360	BWS-G-B	O ₃	0 ppm to 1 ppm	
HZ344	BWS-P-Y	HZ361	BWS-P-B	PH ₃	0 ppm to 5 ppm	
HZ345	BWS-S-Y	HZ362	BWS-S-B	SO ₂	0 ppm to 100 ppm	
WIRELESS						
HZ363	BWS1-C-Y	HZ380	BWS1-C-B	Cl ₂	0 ppm to 100 ppm	
HZ364	BWS1-V-Y	HZ381	BWS1-V-B	ClO ₂	0 ppm to 100 ppm	
HZ365	BWS1-ML-Y	HZ382	BWS1-ML-B	CO	0 ppm to 2000 ppm	
HZ366	BWS1-M2-Y	HZ383	BWS1-M2-B	CO	0 ppm to 2000 ppm	
HZ367	BWS1-E-Y	HZ384	BWS1-E-B	ETO	0 ppm to 50 ppm	
HZ368	BWS1-R-Y	HZ385	BWS1-R-B	H ₂	0 ppm to 1 ppm	
HZ369	BWS1-HL-Y	HZ386	BWS1-HL-B	H ₂ S	0 ppm to 100 ppm	
HZ370	BWS1-H2-Y	HZ387	BWS1-H2-B	H ₂ S ext range	0 ppm to 1000 ppm	
HZ371	BWS1-Z-Y	HZ388	BWS1-Z-B	HCN	0 ppm to 100 ppm	
HZ372	BWS1-A-Y	HZ389	BWS1-A-B	NH ₃	0 ppm to 200 ppm	
HZ373	BWS1-A2-Y	HZ390	BWS1-A2-B	NH ₃ ext range	0 ppm to 500 ppm	
HZ374	BWS1-N-Y	HZ391	BWS1-N-B	Nitric Oxide	0 ppm to 250 ppm	
HZ375	BWS1-D-Y	HZ392	BWS1-D-B	NO ₂	0 ppm to 100 ppm	
HZ376	BWS1-XL-Y	HZ393	BWS1-XL-B	O ₂	0 v/v to 0.3 v/v	
HZ377	BWS1-G-Y	HZ394	BWS1-G-B	O ₃	0 ppm to 1 ppm	
HZ378	BWS1-P-Y	HZ395	BWS1-P-B	PH ₃	0 ppm to 5 ppm	
HZ379	BWS1-S-Y	HZ396	BWS1-S-B	SO ₂	0 ppm to 100 ppm	

GASALERTMAX XT II MULTI-GAS DETECTORS - FIVE UNIT CRADLE CHARGER

- Gas Detector Series: GasAlertMax XT
- Parts: Charger

Model No. **HX926**
Mfg. No. **XT-C01-MC5**
Price/Each **\$**



Honeywell

INTELLIDOX DOCKING STATIONS

- The IntelliDoX system is expandable to five docking modules helping you drive productivity, reliability and efficiency
- Provides a new level of customization for bump testing, configuration and record-keeping in a maintenance-free detector
- Configure alarm set points and change detector settings throughout the operation life of the BW Clip
- Quick and easy setup — great for turnarounds
- Each module has its own easy-to-read LCD screen and keypad for independent operation



Honeywell

Model No.	Mfg. No.	Compatible with	Price/Each
HZ187	DX-CLIP	BW Clip	
HZ286	DX-MCLP	BW MicroClip XL / MicroClip X3	
HZ402	DX-SOLO	BW Solo	
HZ404	DX-ULTRA	BW Ultra	

ACCESSORIES

Model	Mfg. No	Description	Price/Each
HZ188*	DX-ENBL-NA	Enabler Kit	
HZ190	DX-MI-KEY	Multi-Inlet Key, For Solo only	

*Enabler Kit includes power supply with region-specific AC power cord, ethernet cable, inlet (purge) filter assembly, 3 ft. / 1 m calibration gas tubing, 3 ft. / 1 m purge gas tubing, 15 ft. / 4.5 m exhaust tubing, quick connect fittings and IntelliDoX inlet end plate.

MICRODOCK II AUTOMATED INSTRUMENT DOCKING STATIONS

- Fully automatic "hands-free" calibration, functional bump testing, record keeping and charging
- Automatically verifies performance of sensors, as well as audible and visual alarms
- Stores and updates calibration records in the MicroDock II, as well as in data logging instruments
- Quick and easy compliance – simple, automatically maintained accurate records
- Light weight and fully portable with optional wall mount
- Operates via 6-V line power or four C-cell batteries (batteries not included)
- Fully customizable
- Add self-contained docking modules to the system via simple, plug-in connections
- Multiple Microdock II systems can be connected via a LAN
- Includes BW Fleet Manager II software for easy data analysis
- Multi-language support in English, French, German, Spanish, and Portuguese
- One base station with one AC outlet supports up to ten modules to suit your application



MicroDock II shown with assorted docking modules

Honeywell

Model No.	Mfg. No.	Docking Module Type	Price/Each
BASE STATION WITH DOCKING MODULE & CHARGING CABLE			
HX917	DOCK2-2-1C1P-00-G	GasAlertMicroClip XT	
HX909	DOCK2-2-1C1N-00-G	GasAlertQuattro	
HX927	DOCK2-2-1C1M-00-G	GasAlertMax XT	
HX941	DOCK2-2-1C1K-00-G	GasAlertMicro 5	
BASE STATION WITH DOCKING MODULE (NO CHARGING CABLE)			
HX918	DOCK2-2-1P-00-G	GasAlertMicroClip XT	
HX910	DOCK2-2-1N-00-G	GasAlertQuattro	
HX928	DOCK2-2-1M-00-G	GasAlertMax XT	
HX942	DOCK2-2-1J-00-G	GasAlertMicro 5	
DOCKING MODULE ONLY			
HX920	DOCK2-0-1P-00-G	GasAlertMicroClip XT	
HX912	DOCK2-0-1N-00-G	GasAlertQuattro	
HX930	DOCK2-0-1M-00-G	GasAlertMax XT	
HX944	DOCK2-0-1J-00-G	GasAlertMicro 5	