

CHEMICALS

LPS 3® HEAVY-DUTY INHIBITORS

- Protects up to two years
- Stops rust and corrosion
- Provides non-sling lubrication
- Non-flammable propellant
- Self-healing, waxy film
- Provides anti-seize coating
- Safe to use on rubber, fabric, plastics and paints
- Meets or exceeds these specs: Boeing BMS-3 23F Type II, MIL-C-0083933A, para.3.2-3.16, MIL-C-16173D Grade 2 Class I, DMS 2150, Airbus TN A. 007.10138 Type I Grade 2
- Accepted for use in Canadian food processing facilities



Model No.	Mfg. No.	Size	Price /Each
AA808	C00316	11 oz.	
AB559	C00322	20-oz. trigger	
AB558	C03128	1 gal.	
AB556	C00305	5 gal.	
AB557	C00355	55 gal.	

BRIGHT COAT COLD GALVANIZE CORROSION INHIBITORS

- Shiny zinc coating
- Prevents rust and corrosion on all metals
- Restores hot dip galvanizing
- Dries to touch in 15 to 30 minutes
- Repairs rusted, galvanized and welded surfaces
- Electrochemically protects bare metal
- Heat resistant, flexible coating
- Will not yellow, chalk, crack or peel



Model No.	Mfg. No.	Size	Price /Each
AB485	C05916	13 oz.	

BIO-RUST NEUTRAL PH RUST REMOVERS

- Removes rust and other metallic particles
- VOC free, solvent free, non-flammable, pH neutral solution biodegradeable
- Not controlled under WHMIS
- Non-corrosive rust remover
- High workload - can remove 1.5 kg (3.3 lbs.) of iron oxide per 20 L
- For use with iron and mild steel
- Deeply rusted parts may require longer soaking time
- After application of Bio-Rust, rinse parts in water to remove loosened contaminants
- After removing rust, dip pack into fresh bath or Bio-Rust to provide short term corrosion protection
- It is recommended to degrease part before using Bio-Rust
- Bio-Rust is designed for immersion applications only
- Immerse parts in Bio-Rust at room temperature and let react for at least 30 minutes



Model No.	Mfg. No.	Size Litres	Gallons	Price /Each
AD441	53-G247	20	5.2	
AD442	53-G248	208	55	

EVAPO-RUST™ RUST REMOVERS

- Removes rust quickly without scrubbing
- Dipping process
- Non-toxic, non-corrosive, non-flammable
- VOC free
- Water-soluble, biodegradable, safe on skin
- Contains no acids, bases or solvents
- Will not harm unrusted metals



Model No.	Mfg. No.	Size	Price /Each
AD049	ER1	1 L	
AD050	ER4	3.78 L	
AD051	ER20	18.9 L	
AD052	ER205	205 L	

ZINC MATE™

- Flashpoint: -19°C
- Fast evaporation rate
- Working Temperature: 54.4°C (Continuous) and 65.6°C (Intermittent)
- High performance coating of >93% pure zinc that electrochemically bonds with ferrous metals to form a galvanic cell
- Actively fights rust and corrosion
- Use as a touch-up for damaged galvanized coatings



Model No.	Mfg. No.	Size	Price /Each
YA185	73054	369 g	

COLD GALVANISED CORROSION INHIBITORS

- 95% zinc-rich galvanized coating
- Commonly used as a flash rust preventative on welded areas
- Works like a hot-dip on ferrous metals indoors and out
- Three-year protection
- Withstands water temperature up to 212°F (100°C) and continuous dry heat up to 750°F (400°C)
- Flexible coating will not yellow, chalk, crack or peel
- Electrochemically protect bare metal
- Meets or exceeds these specs: MIL-P-46105 Weld Through Primer, Passes Preece Test for Hot-Dip Galvanizing



Model No.	Mfg. No.	Size	Price /Each
AA807	C00516	14-oz.	
AB552	C05128	1 gal.	

WD-40® SPECIALIST™ RUST RELEASE PENETRANT

- Penetrates deep into crevices, threads and seams to break the bonds that hold stuck parts together
- Ideal for use on nuts, bolts, threads and locks
- Leaves behind a protective layer and helps prevent rust and corrosion from re-forming
- Quickly goes to work on rusted nuts, bolts, threads, locks and chains



SPECIALIST

Model No.	Mfg. No.	Size	Price /Each
AF171	01078	311 g	

SP-400™ CORROSION INHIBITOR

- Long-term indoor/outdoor corrosion inhibitor that provides protection of all equipment subject to heat, humidity, chemicals or severely corrosive atmospheres
- Ideal on machined surfaces and assemblies subjected to long periods of storage
- NSF Registered H2



Model No.	Mfg No.	Size	Price /Each
AF108	73282	284 g	

EXTEND® RUST TREATMENTS

- Goes on white and converts rust to a durable, black, metal-protective coating in 10 minutes
- Wirebrush parts and apply with brush or spray
- Surface rust must be present
- Use as a primer or finish coat
- Resists temperatures to 250°F intermittent, 200°F continuous
- Approved by the American Bureau of Shipping



Model No.	Mfg. No.	Size	Price /Each
AA633	234981	1 qt.	
AA634	160802	1 gal.	
AC110	234984	5 gal.	